



**Home of the EZroll off**  
**SPECIFICATIONS DATA FOR**  
**Model EZ16TR**  
**EZroll off Trailer**

<i>Hoist Rated capacity:</i>	16,000 lbs.
<i>Hoist Frame:</i>	3" x 6" x 1/4" wall tube.
<i>Main Frame:</i>	3" x 5" x 3/16" wall tube.
<i>Front Stops:</i>	5/8" Plate.
<i>Safety Lock:</i>	Automatic mechanical.
<i>Hoist Cylinder:</i>	2 - 4" x 48" x 2" Chrome Rods.
<i>Winch Cylinder:</i>	2 - 4" x 48" x 2" Nitro Rods.
<i>Cable:</i>	5/8" Cable.
<i>Outside Rollers:</i>	3" O.D. w/bronze bearing.
<i>Cable Sheaves:</i>	8" O.D. w/bronze bearing.
<i>Cable Travel:</i>	192"
<i>Hinge Shaft:</i>	1-1/2" with grease zerk.
<i>Dump Angle:</i>	51 degrees.
<i>Trailer Weight,Width,Length:</i>	4340 lbs, 101"W, 261"L.
<i>Approximate Operating Times:</i>	- Down 22 sec. - On 53 sec. - Off 47 sec.
<i>Hydraulics:</i>	- All hydraulics have safety lock valves. - Electric over hydraulic with manual override. - <b>Wireless remote controlled operation.</b>
<i>Dumpster Style:</i>	Tub.
<i>Maximum Dumpster Size:</i>	20 cubic yard.
<i>Hitch:</i>	Pintel or Gooseneck.
<i>Jack:</i>	- <b>Hydraulic wireless remote controlled.</b>
<i>Warranty:</i>	- Five-year structural.
<i>Other:</i>	- 13 horse Honda engine -Electric start, backup recoil start, 10/2 gpm pump at 2000 psi. - UHMW slide pulley block. - Dual container locks front and back. - Hydraulic front tongue jack. - Aluminum diamond plate motor cover. - Oil bath hubs on axles. - 235/75R 17.5 16-Ply Load-H (Tires) - Torflex axles 8,000 lbs with electric brakes. - Tread Plate side steps.
<i>Popular Options:</i>	- Semi Auto Tarper - Detachable or weld on Gooseneck

**Note: Materials and product improvement is a continuous commitment at NEDLAND INDUSTRIES, INC. These specifications are subject to change without notice.**

*Mailing address:*

*P.O.Box 217*

*Ridgeland, Wisconsin 54763*

E-mail: [polykan@chibardun.net](mailto:polykan@chibardun.net)  
(715) 949-1982

*Delivery address:*

*315 Railroad Street*

*Ridgeland, Wisconsin 54763*

web: [www.nedland.com](http://www.nedland.com) or [www.ezroll off.com](http://www.ezroll off.com)  
(800) 447-4925 Fax (715) 949-1983