



NSC-200-30

Specifications

Overall Length	22'4"
Overall Width	101"
Overall Height	102"
Container Capacity	30 Cu. Yds.
Compactor capacity	2 Cu. Yds.
Platen Area	60" x 44 x 36"
Charge Opening	42" x 60"
Ram Penetration	12"
Twin Bypass Cylinders	4" x 42" x 2.5"
Line Pressure	2000 PSI
Max Line Pressure	2500 PSI
Max Ram Force	63000 LBS
Cycle Time	45 Seconds
Fluid Capacity	35 Gallons
Pump	10.5 GPM
Motor	10 HP/Tri-Volt, 3 Phase
Approximate Weight	10700 LBS

Options

- 10 HP 220V, 1 Phase
- Fluid Reservoir heater
- Open Hopper (for dock or ground loading)
- Enclosed Doghouse with Door and Interlock
- Walk On or Drive On Deck with 42" Safety Rails
- Side Loading Hoppers
- Through-The-Wall Chutes
- Cart Dumper System
- Container guide rails
- Hydraulic Tailgate

Container features

- 3/16" steel plate floor with 6" x 2" x .25" structural steel tubing rails with .5" x 2" steel bottom wear bars
- 3/16" steel plate side, roof and door
- Full .75" thick door seal
- Side & bottom ratchet latch door hinges with grease fittings
- Double end pick-up (standard with outside rail cable pull)
- Tapered width from 80" at compactor to 88" at door (inside dimensions)
- **Exclusive** side and bottom, door latch system

Compactor Features

- .5" Steel plate floor with 3" structural channels, .25" Steel plate sides with 4" x 2" x .25" & 6" x 2" x .25" structural steel tubing with 6" channel
- Breaker bar 6" x 6" x 1" with retaining teeth
- 6" x 6" x .5" hydraulic cylinder mounts
- 6" Fluid sump with 4" drain
- Replaceable .5" UHMW polyethylene wear bars on ram sides, tops and bottoms for a smooth, quiet and near frictionless operation
- Weatherproof control panel and power pack
- Removable rear & top access panels

Electrical/Hydraulic Features

- (PLC) Controller power unit
- E-Stop button
- Automatic Single Cycle
- Auto/manual Selector
- Key Lock On/Off Switch
- Low Oil Sensor Shutdown
- Multi Cycle
- 80%-100% Full Lights
- Automatic Shutdown with Auto Safety Retract
- 15' remote
- Fluid Filled Pressure gauge
- Inlet Fluid Strainer
- 15' hydraulic hoses
- Left or Right Side Hydraulic Connections



NSC-200-35

Specifications

Overall Length	23'4"
Overall Width	101"
Overall Height	102"
Container Capacity	35 Cu. Yds.
Compactor capacity	2 Cu. Yds.
Platen Area	60" x 44 x 36"
Charge Opening	42" x 60"
Ram Penetration	12"
Twin Bypass Cylinder	4" x 42" x 2.5"
Line Pressure	2000 PSI
Max Line Pressure	2500 PSI
Max Ram Force	63000 LBS
Cycle Time	45 Seconds
Fluid Capacity	35 Gallons
Pump	10.5 GPM
Motor	10 HP/Tri-Volt, 3 Phase
Approximate Weight	10900 LBS

Options

- 10 HP 220V, 1 Phase
- Fluid Reservoir heater
- Open Hopper (for dock or ground loading)
- Enclosed Doghouse with Door and Interlock
- Walk On or Drive On Deck with 42" Safety Rails
- Side Loading Hoppers
- Through-The-Wall Chutes
- Cart Dumper System
- Container guide rails
- Hydraulic Tailgate

Container features

- 3/16" steel plate floor with 6" x 2" x .25" structural steel tubing rails with .5" x 2" steel bottom wear bars
- 3/16" steel plate side, roof and door
- Full .75" thick door seal
- Side & bottom ratchet latch door hinges with grease fittings
- Double end pick-up (standard with outside rail cable pull)
- Tapered width from 80" at compactor to 88" at door (inside dimensions)
- **Exclusive** side and bottom, door latch system

Compactor Features

- .5" Steel plate floor with 3" structural channels, .25" Steel plate sides with 4" x 2" x .25" & 6" x 2" x .25" structural steel tubing with 6" channel
- Breaker bar 6" x 6" x 1" with retaining teeth
- 6" x 6" x .5" hydraulic cylinder mounts
- 6" Fluid sump with 4" drain
- Replaceable .5" UHMW polyethylene wear bars on ram sides, tops and bottoms for a smooth, quiet and near frictionless operation
- Weatherproof control panel and power pack
- Removable rear & top access panels

Electrical/Hydraulic Features

- (PLC) Controller power unit
- E-Stop button
- Automatic Single Cycle
- Auto/manual Selector
- Key Lock On/Off Switch
- Low Oil Sensor Shutdown
- Multi Cycle
- 80%-100% Full Lights
- Automatic Shutdown with Auto Safety Retract
- 15' remote
- Fluid Filled Pressure gauge
- Inlet Fluid Strainer
- 15' hydraulic hoses
- Left or Right Side Hydraulic Connections